



Novo Cult, Hight 1807 mm, Lenght 500 mm, Flame Red

Construction features

steel towel warmer radiator with horizontal elements featuring round tubes

25 mm diameter

side manifolds with semi-oval section 50x36,5 mm

manifold threading and central connections (50 mm) 1/2" Gas right

maximum working pressure 6 bar

maximum working temperature 95°C

Standard equipment

4 adjustable wall fixing brackets in the same color as the radiator

air vent

Certifications



Plus



Technical data

Model	Deph (mm)	Height (mm)	Width (mm)	Conn. C. (mm)	Weigth (kg)	Capacity (lt)	Δt=50°C (kcal/h)	Δt=50°C (Watt)	Δt=40°C (Watt)	Δt=30°C (Watt)	Δt=20°C (Watt)	Exponent	mixed oper. (Watt)
807 15 tubi 1 intervallo	44,0	807	450	406	7,80	5,60	336,0	391,0	297,0	209,0	127,0	1,226	400
807 15 tubi 1 intervallo	44,0	807	500	456	8,40	6,10	370,0	430,0	327,0	229,0	139,0	1,229	400
807 15 tubi 1 intervallo	44,0	807	600	556	9,60	7,00	436,0	507,0	385,0	270,0	163,0	1,236	400
1207 23 tubi 2 intervalli	44,0	1207	450	406	11,00	8,00	479,0	557,0	420,0	292,0	175,0	1,262	400
1207 23 tubi 2 intervalli	44,0	1207	500	456	11,80	8,60	525,0	610,0	460,0	320,0	192,0	1,260	400
1207 23 tubi 2 intervalli	44,0	1207	600	556	13,50	9,90	617,0	718,0	542,0	378,0	227,0	1,258	700
1567 30 tubi 3 intervalli	44,0	1567	450	406	13,90	10,10	622,0	723,0	545,0	379,0	227,0	1,265	700
1567 30 tubi 3 intervalli	44,0	1567	500	456	14,90	10,80	683,0	794,0	599,0	416,0	249,0	1,264	700
1567 30 tubi 3 intervalli	44,0	1567	600	556	16,90	12,40	805,0	936,0	706,0	491,0	294,0	1,263	1000
1807 36 tubi 3 intervalli	44,0	1807	450	406	16,00	11,70	724,0	842,0	636,0	443,0	266,0	1,258	700
1807 36 tubi 3 intervalli	44,0	1807	500	456	17,20	12,60	798,0	928,0	701,0	489,0	294,0	1,255	1000
1807 36 tubi 3 intervalli	44,0	1807	600	556	19,60	14,40	945,0	1.099,0	831,0	580,0	349,0	1,250	1000

Thanks to the high performance of Irsap Novo Cult radiators, the ideal Δt for low temperature projects is Δt at 30°C.

For Δt different from 50°C use the formula: $Q=Q_n (\Delta t / 50)^n$

Standard equipment

- 4 adjustable wall fixing brackets in the same color as the radiator
- air vent

Packing

The attention that Irsap lavishes on each radiator is also evident in the care given to packaging. Every radiator is protected with packaging caps in shockresistant material; this extra protection prevents damage and scratching during both shipping and handling onsite. All the packaging must be disposed in conformity with the regulations in force, acknowledged by the respective bodies.